



MAST for Publishers Add Pubsite API Methods

Below describes the methods used to add a publisher site to a network, set zones within created sites, request network IDs and request site IDs. All 4 methods are described below.

Method: addSiteToNetwork		
Parameter	Description	Code Example
privatekey	The unique identifier that allows access to the user account.	privatekey=3x56eEr
network_id	The ID of the network the site is being added to.	network_id=888
site_name	The name of the site being added to the network.	site_name= My Mobile Site
site_url	The URL of the site being added to the network.	site_url=www.url.com
channel_id*	The ID of the channel(s) the site is being categorized in.	channel_id=1

Channel IDs:

For pre-existing channels supported by the mOcean Mobile platform.

id	name
18	Technology
19	Communications
2	Downloads
3	Communities
4	Entertainment and Gaming
5	News and Info
6	Portals
8	Auto
9	Travel
10	Business and Finance
11	Weather
12	Health
13	Women
14	Shopping

Method: addZoneToSite		
Parameter	Description	Code Example
privatekey	The unique identifier that allows access to the user account.	privatekey=3x56eEr
pubsite_id	The ID of the publisher site. Can be generated with AddSiteToNetwork method.	pubsite_id=999
zone_name	The name of the zone being created.	zone_name=TopBanner
description	A description of the zone being created.	description=Top banner placement
zone_type (optional)	The type of zone being created, either text or banner.	zone_type=text

Method: getNetworkId		
Parameter	Description	Code Example
privatekey	The unique identifier that allows access to the user account.	privatekey=3x56eEr
subdomain (optional)	The subdomain of the network the ID is being requested for. If not passed, a list of all subdomains and corresponding IDs will be returned.	subdomain=test

Method: getSiteId		
Parameter	Description	Code Example
privatekey	The unique identifier that allows access to the user account.	privatekey=3x56eEr
siteurl (optional)	The URL of the site the ID is being requested for. If not passed, a list of all sites and corresponding IDs will be returned.	siteurl= newurl66 (returns any match)

Sample Code:

Method: addSiteToNetwork

http://moceanmobile.net/mocean_rest_server.php?method=addSiteToNetwork&privatekey=3x56eEr&network_id=888&site_name=newsite&site_url=www.newurl.com&description=newdesc&channel_id=1

```
<xml>
<site>6208</site>
</xml>
```

Valid response will be the above with your new site id.

Method: addZoneToSite

http://moceanmobile.net/mocean_rest_server.php?method=addZoneToSite&privatekey=3x56Er&pubsite_id=999&zone_name=mynewzone2&description=newdesc2

(optional)

&zone_type=text

or

&zone_type=banner

```
<xml>
<zone>6208</zone>
</xml>
```

Valid response will be the above with your new zone id.

Method: getNetworkId

http://www.moceanmobile.com/mocean_rest_server.php?method=getNetworkId&privatekey=3x56Er

subdomain (optional)

```
<network>
<subdomain>test</subdomain>
<id>141</id>
</network>
```

Valid response will be the above with your network id.

Method: getSiteId

http://www.moceanmobile.com/mocean_rest_server.php?method=getSiteId&privatekey=3x56Er

siteurl (optional)

```
<site>
<domain>newurl66 </domain>
<id>5341</id>
</site>
```

Valid response will be the above with your site id.